

On page 7, line 2, please delete the word "Side" and insert the word - - side- - as follows:

FIGURE 6 depicts a top view of the divider panel in its assembled configuration as integrated from the liner side wall.

On page 8, line 2, please delete the word "Side" and insert the word - - side- - as follows:

FIGURE 14 depicts another alternate embodiment in its assembled configuration as formed from the liner bottom and side wall.

On page 8, line 5, please delete the word "Side" and insert the word - - side- - as follows:

FIGURE 15 depicts a top view of the alternate embodiment of Figure 14 in which the liner bottom is used in conjunction with multiple living hinges to form a trunk storage compartment with the side wall.

On page 8, line 11, please delete the word "Side" and insert the word - - side- - as follows:

FIGURE 16 depicts a rear view of the alternate embodiment in which the enclosure and divider panels are raised from the horizontal position prior to forming the trunk storage compartment with the liner side wall.

On page 8, line 13, please delete the word "Side" and insert the word - - side- - as follows:

FIGURE 17 depicts a top view of the divider panel with a living hinge within the liner bottom and liner side wall to create the sides of the trunk storage compartment with the enclosure panel being formed from the liner front wall.

On page 8, line 16, please delete the word "Side" and insert the word - - side- - as follows:

Figure 18 depicts a rear view of the divider panel raised from the horizontal position from the liner bottom and the enclosure panel in the liner side wall being raised to form the trunk storage compartment.

On page 9, beginning at line 17 and continuing in that paragraph through its end on page 10, line 5, please delete the word "Side" and insert the word - - side- - as follows:

The truck bed liner is molded to generally fit the contours of a truck bed, including wheel well shrouds 42. Liner bottom 40 is co-formed to liner front wall 34 at 48. Liner bottom 40 is co-formed to liner side walls 36, 38 at 50 beginning at a point adjacent liner front wall 34 to a first predetermined point on side walls 36, 38. At the first predetermined point is found living hinge 52. Living hinge 52 extends from liner side wall 36 to opposite liner side wall 38. Liner bottom 40 extends to the rear of a living hinge 52 to a second predetermined point 53. Between living hinge 52 and second predetermined point 53, liner bottom 40 is not attached to liner side walls 36, 38. At second predetermined point 53 is found free edge 54. Free edge 54 extends from liner side wall 36 to liner side wall 38. Along free edge 54 is optionally found horizontal

protrusion 55 along its edge. Horizontal protrusion 55 provides strength to the divider. The perimeter formed by the unattached portion of liner bottom 40 and living hinge 52 comprises divider panel 56.

On page 12, beginning at line 5 and continuing in that paragraph through its end at line 12, please delete the word "Side" and insert the word - - side- - as follows:

Figure 5 illustrates that divider panel 56 may also be molded or cut into the liner side walls 36, 38 of truck bed liner 20. In this embodiment, divider panel 56 is formed into one wall, either liner side wall 36 or liner side wall 38, which permits divider panel 56 to pivot about living hinge 52 on the vertical axis and then be secured into place by a divider lock means 58 found on the opposite liner side wall as illustrated in Figure 6. The disadvantage of this embodiment is that the side wall surface available to mold or cut a divider may not be sufficient to completely bridge liner bottom 40 between liner side wall 36 and liner side wall 38 of truck bed liner 20. To address this problem, two divider panels, each of which are of a length equal to one-half the width of the liner may be used. In this manner, the two divider panels can join in the center of the bed to form a single divider panel.

On page 12, line 1, please delete the number "4" and insert the number - - 9 - - as follows:

Figure 9, latch means 59 protrudes from each liner side wall 36, 39 near the lower aspect of each side wall.

On page 16, beginning at line 7 and continuing in that paragraph through its end at line 8, please delete the word "Side" and insert the word - - side- - as follows:

This alternate embodiment may also be accomplished using the same inventive concept as illustrated in Figure 17 by providing liner bottom 40 with a divider panel 56 and a living hinge 52 and liner side wall 36 or liner side wall 38 with a side panel 98 to form the sides of the truck storage compartment with enclosure panel 92 being located within liner front wall 34.

On page 16, beginning at line 9, please insert the word - - As illustrated in Figure 18, yet another- - amend the paragraph as follows:

As illustrated in Figure 18, yet another embodiment may also be accomplished without liner side wall 36, 38 providing a side panel 98 (of Figure 17). Instead, the side walls provide an enclosure panel 92 that has a living hinge 52 located on liner side walls 36 or 38 to rotate from a vertical position to a horizontal position for attachment to latch means 96 located along front liner wall 34 with divider panel 56 being rotated to a vertical position from its horizontal position within liner bottom 40.